### MAINE DEPARTMENT OF ENVIRONMENTAL PROTECTION

### **ANNUAL CSO PROGRESS REPORT FOR 2002**

Doc Num: DEPLW0059-D2002 Rev Date: 12/11/02

Permittee:Address:	_ Telephone No.
	NA ' I' NI
1. Information on Combined Sewer System	
A. Current sewered population	
B. Current number of residential users	
C. Current number of commercial/industrial	users
D. Current average residential user charge _	(\$/year)
E. Median Household Income (MHI)	(\$/year)
F. Current residential user charge is	% of MHI
G. Original number of CSOs at beginning of	f abatement program
H. Current number of CSOs	_
I. Percent reduction of CSO points to date	
J. List any CSOs removed in reporting year	
CSO # Name	
	_
K. Total sewer footage feet	
L. Original % combined sewer to total	%
M. Current % combined sewer to total	%
N. Percent reduction of combined sewer	%

### 2. CSO Progress

A.	Current Approved Schedule. (If you have an approved schedule,	it is attached as a paper.)
B.	If existing schedule is behind the approved schedule, list the reaso proposes to catch up in order to comply with the approved schedu	· · · · · · · · · · · · · · · · · · ·
C.	List major accomplishments last year to reduce or abate CSOs	
	Project Estimate of f	low reductions
D.	Costs:	
	<ol> <li>Total original cost estimate for complete program from CSO Master Plan</li> <li>Total cost of CSO abatement to date</li> <li>Percent complete by cost (2 / 1 above)</li> <li>Total SRF loans to date</li> <li>Total cost of CSO projects in reporting year</li> <li>Anticipated budget for CSO projects next year</li> <li>Sewer O&amp;M budget in reporting year</li> <li>Anticipated sewer O&amp;M budget for next year</li> <li>Estimated CSO needs for next five years (include cost in no.6)</li> </ol>	\$
E.	Private inflow sources:  1) Has a house to house survey been done? 2) If yes, when? 3) If no, is one planned? 4) When? 5) Roof leaders removed date 6) Roof leaders removed in reporting year 7) Known roof leaders remaining in system 8) Basement sump pumps removed to date 9) Basement sump pumps removed in reporting year 10) Known sump pumps remaining in system 11) Number of known foundation drains to system	Yes No
	12) Do you charge a surcharge for private sources? 13) If yes, how much?	Yes No

F.	Other	inflow sources	
	1) Nı	umber of catch basins removed this yea	r
		imber of catch basins remaining in syst	
		etlands/bogs draining to sewer?	Yes No
		reams intercepted by sewer?	Yes No
		* *	eal with them?
	_	,	
G.		• •	termine effectiveness of previous CSO abatement th projections made during the CSO Master Plan.
Н.	(Enter Work 1) Re	r precipitation, CSO events, volumes, or data on Excel spreadsheet Csoflows.x done on the Nine Minimum Controls of esults of operation and maintenance (Ower system overflows during the year.	ls)
	a.	Who is responsible for combined sew	er system O&M?
		Name	Tel. No
		Title	
		DeptSize Staff	
	b.	Inspection schedules	
		Number of CSO regulators	Inspector intervals
		Number of tide gates	Inspector intervals
		Number of pump stations	
		Number of CSO outfalls	Inspector intervals

c. Document the following activities that were performed and include the tons of debris removed last year from catch basins and sewers. (Not all activities may apply to your system. Please use N/A when appropriate.)

Catch Basin Cleaning		
Total # of Basins Last Year	# of Basins Cleaned Last Year	Debris Removed  Tons or cu. yds.
(Please attach cleaning sche	edule if available)	
Sewer Cleaning		
Total Combined Sewer	Footage Cleaned Last Year	
(Please attach cleaning sche	edule if available)	Tons or cu. yds
Pump Station Cleaning		
Cleaning Frequency	Inspection Frequency	
TV Work		
Sewer Footage Televised lin. ft.	TV Frequency	
Smoke Testing		
Sewer Footage Smoke Tes lin. ft.	ted Dates of Smoke Te	sting
Infiltration/Inflow Study		
Sewer Footage Study Was lin. ft.	Performed On	

2) Maximum Use of the Collection System for Storage

Maximum use of the collection system for storage means making relatively simple modifications to the combined sewer system to enable the system itself to store wet weather flows until downstream sewers and treatment facilities can handle them. The municipality should evaluate more complex modifications as part of the long-term control plan.

	cument attempts last year to retard in a control type devices.	inflows to the system by use of special gratings of
Nur	mber of Special Storm Drain Gratin	e e e e e e e e e e e e e e e e e e e
Nur Inst	mber of Flow Control Type Devices	
Nui Inst Cor	mber of Flow Control Type Devices	8

3) Review and Modification of the Industrial Pretreatment Program to Assure that CSO Impacts Are Minimized

The municipality should determine whether nondomestic sources are contributing to CSO impact and, if so, investigate ways to control them. The objective of this control is to minimize the impacts of discharges into combined sewer systems from significant nondomestic sources (i.e., industrial and commercial sources during wet weather events, and to minimize CSO occurrences by modifying inspection, reporting, and oversight procedures within the approved pretreatment program.

# Fill in this section only if you have nondomestic source of wastewater.

Do you have an industry that significantly impacts a CSO?	Yes	No	
What measures or modifications were taken last year to insurcontributing to CSO impacts. (Examples of measures: Inventhe combined sewer, assessment of nondomestic discharges of modifications)	tory of non	domestic discha	rges to
Maximization of Flow to the POTW for Treatment			

Maximizing flow to the POTW entails simple modifications to the combined sewer system and treatment plant to enable as much wet weather flow as possible to reach the treatment plant. The objective of this minimum control is to reduce the magnitude, frequency, and duration of CSOs that flow untreated into receiving waters.

a. List any change, completed or planned last year to maximize flow to the POTW.

PLANNED PHYSICAL CHANGE	ESTIMATED COST	ESTIMATED COMPLETION DATE	ESTIMATED YEARLY DECREASE IN EVENTS	ESTIMATED YEARLY DECREASE IN VOLUME (MGD)
	_	_	_	_

#### 5) Prohibition of CSO Discharges During Dry Weather

This control includes all measures taken to ensure that the combined sewer system does not overflow during dry weather flow conditions. Dry weather overflow control measures include improved O&M as well as physical changes to regulator and overflow devices.

a.	If yes, explain.	ie last year?	Yes	No	
b.	What measures are planned to prevent further	dry weather	overflow	s?	
Co	ontrol of Solid and Floatable Material in CSO Di	scharges			
im	e intent of this control is to document that low of plemented which reduce solids and floatables dacticable.				
a.	List any of the following control measures that and floatables discharged from CSOs.	t were imple	emented la	st year to 1	reduce solids
	Baffles in regulators or overflow structures:				
	Number of Baffles Installed:	Success:	Good	Fair	Poor
	Trash Racks in CSO discharge structures:  Number of Trash Racks Installed:	Success:	Good	Fair	Poor
	Catch basin modifications:				
	Number of Modifications Installed:	Success:	Good	Fair	Poor
	End of pipe nets:  Number of Nets Installed	Successi	Good	Fair	Poor
		Buccess.	J004	1 a11	1 001
	Litter Controls:  Liter Control: Yes No	Success:	Good	Fair	Poor

6)

Doc Num: DEPLW0059-D2002 7 Rev Date: 12/11/02

		Other Controls:			
		Type of Control	Success: Good	Fair	_ Poor
		The estimated amount of solids and floatab control measures.	les removed last year by	implementir	g the above
		tons or cu. yds.			
		(Attach any schedules and associated costs	for implementation of th	is control.)	
7)	Pol	llution Prevention Programs That Focus on	Contaminant Reduction	Activities	
		e seventh minimum control, pollution preve tering the combined sewer system and thus t	-		nts from
	a.	Document any of the following efforts last	year to implement this co	ontrol.	
		Public education or increased awareness pr could decrease dry weather sanitary flow to weather flows that can be treated at the PC	the POTW and increase		
		The placement of garbage receptacles, more ducation you have implemented.	re efficient garbage collec	ction, or thro	ough public
		Street sweeping efforts with estimate of ma	aterial removed.	tons	or cu. yds.

Efforts to eliminate illegal dumping. Programs such as law enforcement and public education aimed at controlling illegal dumping of litter, tires, and other materials into wat bodies or onto the ground.
Does the community have a hazardous waste collection program? Yes No If yes, how often is it done and how much hazardous waste is collected?
List and describe any measures planned or implemented for the installation of best management practices (BMP) to reduce pollutants in stormwater runoff.
List and describe other pollution prevention measures planned for implementation and the names of individuals or departments responsible. Attach any schedules and cost estimates associated with this control.

8) Public Notification to Ensure That the Public Receives Adequate Notification of CSO Occurrences and CSO Impacts

The objective of this control is to ensure that the public receives adequate notification of CSO impacts on pertinent water use areas. Of particular concern are beach and recreational areas that are affected by pollutants discharged in CSOs.

a.	Locations where signs are posted.
	CSO outfalls:Other:
b.	List dates of CSO informational public hearings or meetings last year.
c.	List any other measures to inform the public that occurred last year.
Mo	onitoring to Effectively Characterize CSO Impacts and the Effectiveness of CSO Controls
the	e ninth minimum control involves visual inspection and other simple methods to determine coccurrence and apparent impacts of CSOs. This minimum control is an initial
ove she	aracterization of the combined sewer system to collect and document information on erflow occurrences and known water quality problems and incidents, such as beach or ellfish bed closures, that reflect use impairments caused by CSOs. Changes in the currences of such incidents can provide a preliminary indication of the effectiveness of the me Minimum Controls.
a.	Check off and fill in information on the following monitoring methods used in overflow structures:
	Flow Meters Locations Frequency Data Collected
	<del></del>

9)

<u>Blocks</u>	
Locations	Inspection Frequency
<u>Chalklines</u> Locations	Inspection Frequency
Other monitoring methods?	
Was a SWMM model developed? Is the model used to report occurrences? Has it been updated to reflect changes:	Yes No Yes No Yes No
CSO impacts to swimming beaches and shell List any swimming beaches that may be impacted that may be impacted as a second	_
Does your community or other entity test the Yes No Frequency?	± *
If yes, list dates of test and results Dates	Results
Any beach closing last year?	Yes No SOs? Yes No
Were they caused, in whole or in part by CS	303. 1 <b>c</b> 5 110

Doc Num: DEPLW0059-D2002 11 Rev Date: 12/11/02

	Open	Conditionally Opened	Closed	
	Any shellfish areas closed If yes, list dates:	last year? Yes No		
	If yes, were the closures ca	aused, in whole or in part by CSO wing any swimming beaches or sh	Os? Yes No	
		ny receiving water quality tests o	or CSO sampling tests done la	
4	•	v commercial or industrial flows	added during the year, along contributing to CSO flows.	

ζ.	To assist the DEP in making this form easier to use in future years, please list your computer capabilities:
	Processor capability:
	Operating system (Windows version):
	Word processing program and version:
	Spreadsheet program and version:
	Database program and version:
	E-mail capability and address:
	Do you plan to upgrade hardware or software in 2002, and if so with what?  (Note: DEP uses Windows 95 and Office 97 with Word, Excel and Access)
	Please add any other information on CSOs that you feel is important, but the form did not allow for.